


MLP2462Sx Cat.6 Connecting Hardware 24P STP 0.5U Patch Panel



Factory full compliance!



Specification:

Screened Category 6 ISO/IEC,
EN & TIA Connecting Hardware
ISO/IEC 11801 Ed 2.2
EN 50173-1:2011, ANSI/TIA-568-C.2
IEC 60603-7-4 Ed 2, IEC 60512-27-100(Draft)

Electrical:

Current Rating: 1.5 Amps
Insulation Resistance: 500 Mohms Minimum
Contact Resistance: 10 mohms Maximum
DC Resistance: 0.1 ohms Maximum
Shield Transfer Impedance @ 100 MHz 2000 mohms Max.

Mechanical:

Plug Insertion Life: 750 Cycles Minimum
Plug & Jack Contact Force: 100 Grams Minimum
Using FCC-Approved Plug
Plug Retention Force: 30 lbs Minimum
Temperature: -40° to 150°F (-40° to 68°C)

Physicals:

Frame : 1.5t SPCC, nickel plating
Shield : 0.25mm thickness copper alloy plated with tin
Plastic : High impact flame retardant plastic,
PCB: FR4, 1.0mm Thickness
Jack Wiring: Ø0.46mm phosphor bronze gold over nickel plating
Connector: Insulation displacement connector
(IDC) Accept AWG 22-26 solid wire
Covershielded: 1.0t SPCC, nickel plating

