


SBC

PMB-901LF

ATX MB with Intel® Xeon® E3 V2 and Core™ i3 with VGA/DP, 4 COM, Dual LAN, DDR3

Features :

- LGA 1155 Intel® Xeon® E3 V2 and 3rd Gen. Core™ i3 Processor
- Equipped with Intel® C216 chipset
- Memory supports DDR3 1066/ 1333 DIMM up to 32GB (ECC and non ECC)
- Support Dual Gb Ethernet
- Supports SATA RAID 0, 1, 5, 10
- Expansion Slots for one PCI-E(16x), two PCI-E(4x), four PCI slot



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714- 996-7200 FAX: +1-714- 996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.


OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>



ISO CERTIFIED
9001 14001

PMB-901LF

ATX MB with Intel® Xeon® E3 V2 and Core™ i3 with VGA/DP,
4 COM, Dual LAN, DDR3



Specifications

System

CPU Support	Intel® Xeon® E3 V2 and 3 rd Gen. Core™ i3 processor
CPU Frequency	3.2~3.5GHz
Chipset	Intel® PCH C216
DRAM	4 x 240-pin DDR3 DIMM, support dual -channel 1333/1066Hz SDRAM ECC and Non-ECC Unbuffered DIMM (system max. 32GB)
BIOS	AMI BIOS
Watchdog	1~255 secs Watchdog timer selectable
Power Supply	Support ATX Power
Power Requirement	+5V, +12V, -12V, +3.3V, +5VSB
Dimension	305 mm x 244 mm (12" x 9.6")
Certificate	FCC / CE

I/O Chipset

SATA Interface	2 x SATA III (6.0Gb/s), 4 x SATA II (3.0Gb/s), (Raid 0, 1, 10, 5)
Expansion BUS	1 x PCI-E(16x) , 2 x PCI-E(4x) , 4 x PCI slot
TPM	TPM1.2 with 20-pin header on board for TPM (Trusted Platform Module)
Serial Port	4 x COM port, COM 1/3/4 for RS-232, COM 2 for RS-232/422/485
Parallel Port	1 x parallel port (SPP/EPP/ECP)
IrDA	1 (SIR)

Keyboard	PS/2 Connector, with mini DIN connector
Mouse	PS/2 Connector, with mini DIN connector
LAN	LAN 1: Intel® 82579LM (10/100/1000 Mbps) LAN 2: Intel® 82583V (10/100/1000 Mbps) Support Wake-on-LAN with ATX power
Audio	High Definition Audio; Realtek ALC888S with Mic / Line-In / Line-Out
DI/O	8 in / 8 out
USB	10 x USB 2.0, 2 x USB 3.0

Display

Graphics	Build-in processor, share system memory Supports VGA, Display port
-----------------	---

*Discrete graphic card is necessary for display if the chosen CPU doesn't have integrated graphics support.

Environment

Operation Temp.	0° ~ 60° C (32° ~ 140° F)
Storage Temp.	- 40° ~ 85° C (- 40° ~ 185° F)
Humidity	Operation humidity 5 ~ 90% (non-condensing)

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

Ordering Information

BA-0901	ATX MB with Intel® Xeon® E3 and Core™ i3 (LGA1155) with C216 / VGA / Audio / 2LAN(1G) / 4COM/ Raid
----------------	--

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd.
All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in May 2012.