



**PSGS-2612: 8-Port GbE UTP with PoE + 2-Port GbE UTP without PoE + 2-Port (100/1G) SFP L2 Plus Managed Switch**

### Key Features

- L2+ features provide better manageability, security, QoS, and performance
- Dual speed SFPs for FE or GbE fiber uplink
- 802.3az Energy Efficient Ethernet standard
- IPv6 and s-Flow supports
- Easy-Port-Configuration for ease of setup in the IP Phone, IP Camera or Wireless environment
- Supports 802.3at high power PoE plus standard

### Overview

The PSGS-2612, the next generation L2+ managed PoE switch, from Rubytch, provides a reliable infrastructure for your business network. This switch delivers more intelligent features you need to improve the availability of your critical business applications, protects your sensitive information, and optimizes your network bandwidth to deliver information and applications more effectively. With PoE (Power over Ethernet) function built in, it provides the ideal combination of affordability and capabilities for entry level networking of small business or enterprise which demands IP Phone, IP Camera or Wireless applications, thus helps you create a more efficient, better-connected workforce.

### Applications

Whether you want to create a high-performance network to connect all clients' computers or an application to deliver data, voice, and video services, the PSGS-2612 provides a solution to fit your requirements. Possible implement scenarios include:

#### • Secure and High Performance PC or laptop connectivity:

The PSGS-2612 switch can easily and securely connect clients' PC or laptop in offices with each other and with all of the servers, printers, and other networking devices they use. High performance and reliable connectivity will help to speed file transfers and data processing, improves network performance and security, and keeps the clients connected and productive.

#### • Secure and Quality wireless connectivity:

The PSGS-2612 switch connected with WiFi APs allow WiFi clients to work from conference rooms and public areas, collaborate in any place, and access networking from wherever they are. Gigabit Ethernet connectivity provides these clients have the suitable bandwidth and quality performance they need to make mobility connected. Through embedded security, the clients can work with confidence and authorized users can access networking and network devices.

#### • Unified communications with open standards:

To be a managed network solution, it provides the high performance and advanced networking quality to deliver all networking communications and data (such as IP telephony, IP surveillance, and Video Streaming) over a single network.

#### • Advanced network security:

The PSGS-2612 Switch provides enhanced and advanced network security to guests in public or private area, such as a hotel, an office lobby, or any area open to guests. Using powerful but simple to install security and traffic separating abilities, through guest VLAN or guest access control technology, it will help you to isolate vital networking traffic from guest services and keep guests' network sessions private from each other.

### Benefits

The PSGS-2612 provides security, performance, quality of services, central management and other network control capabilities. Optimized and customized design and affordable pricing, it best fit for SMB or entry-level enterprise solution. It provides:

#### • Excellent performance and reliability:

The PSGS-2612 passed the rigorously testing to deliver excellent performance. As a managed switching solution, it also provide the flexibility to manage and prioritize suitable-bandwidth traffic such as voice.

#### • Easy, simple deployment and configuration:

The device manager software provides an intuitive, web-based interface to simplify deployment, advanced security (ACLs, IP Source guard, VLAN...etc), and quality of service (QoS) traffic prioritization. It

also provides a standard protocol that works through a simple network managed system software (RubyView) to discover RubyTech's devices in the network and display basic information. This switch uses IEEE802.1AB LLDP to automatically discover all the devices (those support LLDP) connected to the network. For more advanced capabilities and Easy-to-use graphical tools, such as ECP (Easy-Port-Configuration), provides preset options for easily configuring each port of the switch, it will make setup easy when operating with IP phones, IP cameras or Wifi APs. The tree CLI architecture will greatly save your time on the network deployment, management and troubleshooting.

- **Strong security:** The switch provides an advanced security and gives you tight control to safeguard the network from unauthorized users. Advanced security features include:
  - Secure remote management by supporting **SSH, SSL** and **SNMPv3** connection which encrypt the packet content at each session.
  - Extensive access control lists (ACLs) to restrict sensitive portions of the network from unauthorized users or guests.
  - Guest virtual LANs (VLANs) provide Internet connectivity to guests while isolating critical traffic from guest traffic.
  - IP Source Guard to prevent datagrams with spoofed addresses from being in the network.
  - IEEE802.1X port security to tightly limit access to specific segments of network.
- **Voice support:**  
The switch can be easily configured with the specific VLAN and QoS parameters to prioritize voice traffic whereas ensure consistent network performance for all services.
- **Advanced network management capabilities:**  
As a managed switch, it helps you to use a variety of advanced managing features to manage traffic over your network. Features include:
  - Support IPv6:** As the IP network addressing scheme evolves to accommodate more devices, PSGS-2612 supports IPv6, the newest version of the Internet Protocol, as well as the previous IPv4 standard. As the result, you have the ability to move up to the next generation of networking applications without an extensive equipment up grade.
  - Remote management:** Using Simple Network Management Protocol (SNMP) and IEEE802.1AB LLDP, you can configure and manage PSGS-2612 and other Rubytch switches in the network remotely, instead of having to directly connect to them.
- **Energy efficiency:** PSGS-2612 is designed to comply with IEEE802.3az, energy efficient Ethernet protocol, reducing energy costs without compromising performance. Power-saving features include:
  - The latest application-specific integrated circuits (ASICs), using low-power technology, allow for lower power consumption and thinner, more efficient designs.
  - Embedded intelligence to adjust signal strength based on cable length.
- **Expansion ports:**  
Featuring 8 Gigabit UTP ports, the PSGS-2612 also offers two SFP ports for uplinks to Fast Ethernet or Gigabit Ethernet fiber optic networks.
- **PoE Save Your Power Infrastructure Cost:**  
8-PoE ports allow power to be supplied to end devices, such as Wireless Access Points or VoIP Phones, directly through the existing LAN cables. By supplying the power end-span, you can centralize power distribution and backup without the need to increase infrastructure. The switch is IEEE 802.3at/af-compliant for Power over Ethernet and provide up to 30 W per port.

**Product Specifications**

Feature	Description		
<b>Performance</b>			
	<b>Model Name</b>	<b>Capacity in Millions of Packets per Second (mpps) (64-byte packets)</b>	<b>Switching Capacity in Gigabits per Second (Gbps)</b>
<b>Switching capacity and forwarding rate</b>	PSGS-2612	17.86	24
<b>Layer 2 Switching</b>			
<b>Spanning Tree Protocol (STP)</b>	Standard Spanning Tree 802.1d Rapid Spanning Tree (RSTP) 802.1w Multiple Spanning Tree (MSTP) 802.1s		
<b>Trunking</b>	Link Aggregation Control Protocol (LACP) IEEE 802.3ad <ul style="list-style-type: none"> <li>• Up to 6 groups</li> <li>• Up to 8 ports per group</li> </ul>		
<b>VLAN</b>	Support for up to 4K VLANs simultaneously (out of 4096 VLAN IDs) <ul style="list-style-type: none"> <li>• Port-based VLAN</li> <li>• 802.1Q tag-based VLAN</li> </ul>		

Feature	Description
	<ul style="list-style-type: none"> <li>• MAC-based VLAN</li> <li>• Management VLAN</li> <li>• Private VLAN Edge (PVE)</li> </ul>
<b>Voice VLAN</b>	Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS
<b>Generic VLAN Registration (GVRP)</b>	Protocols for automatically propagating and configuring VLANs in a bridged domain
<b>DHCP Relay (Layer 2)</b>	Relay of DHCP traffic to DHCP server in different VLAN. Works with DHCP Option 82
<b>IGMP v1/v2/v3 snooping</b>	IGMP limits bandwidth-intensive multicast traffic to only the requesters; supports 1024 multicast groups (source-specific multicasting is also supported)
<b>IGMP Querier</b>	IGMP querier is used to support a Layer 2 multicast domain of snooping switches in the absence of a multicast router.
<b>IGMP Proxy</b>	Support IGMP Proxy
<b>MLD v1/v2 snooping</b>	Deliver IPv6 multicast packets only to the required receivers
<b>Security</b>	
<b>Secure Shell (SSH) Protocol</b>	SSH secures Telnet traffic in or out the switch, SSH v1 and v2 are supported
<b>Secure Sockets Layer (SSL)</b>	SSL Support: Encrypts the http traffic, allowing advance secure access to the browser-based management GUI in the switch
<b>IEEE 802.1X</b>	IEEE 802.1X: RADIUS authentication, authorization and accounting, MD5 hash, guest VLAN, single/multiple host mode and single/multiple sessions Supports IGMP-RADIUS based 802.1X Dynamic VLAN assignment
<b>Layer 2 isolation Private VLAN Edge (PVE)</b>	PVE (also known as protected ports) provides L2 isolation between clients in the same VLAN, supports multiple uplinks
<b>Port Security</b>	Locks MAC Addresses to ports, and limits the number of learned MAC addresses
<b>IP Source Guard</b>	Supports illegal IP address to access to specific port in the switch
<b>RADIUS/ TACACS+</b>	Supports RADIUS and TACACS+ authentication. Switch as a client
<b>Storm control</b>	Broadcast, multicast, and unknown unicast
<b>ACLs</b>	Support for up to 256 entries Drop or rate limitation based on source and destination MAC, VLAN ID or IP address, protocol, port, differentiated services code point (DSCP) / IP precedence, TCP/ UDP source and destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP) packets, IGMP packets, TCP flag
<b>Quality of Service</b>	
<b>Hardware Priority Queue</b>	Support 8 hardware queues
<b>Scheduling</b>	Strict priority and weighted round-robin (WRR) Queue assignment based on DSCP and class of service (802.1p/ CoS)
<b>Classification</b>	Port based; 802.1p VLAN priority based; IPv4/IPv6 precedence/ type of service (ToS) / DSCP based; Differentiated Services (DiffServ); classification and re-marking ACLs, trusted QoS
<b>Rate Limiting</b>	Ingress policer; egress shaping and rate control; per VLAN, per port and flow based
<b>IPv6 applications</b>	Web/ SSL, Telnet/ SSH, ping, Simple Network Time Protocol (SNTP), Trivial File Transfer Protocol (TFTP), SNMP, Syslog
<b>Management</b>	
<b>Web GUI interface</b>	Built-in switch configuration utility for browser-based device configuration (HTTP/ HTTPS). Supports configuration, system dashboard, maintenance, and monitoring
<b>Dual Image</b>	Dual image provides independent primary and secondary OS files for backup while upgrading
<b>SNMP</b>	SNMP version 1, 2c and 3 with support for traps, and SNMP version 3 user-based security model (USM)
<b>Remote Monitoring (RMON)</b>	Embedded RMON software agent supports RMON groups 1, 2, 3, 9 (history, statistics, alarms, and events) for enhanced traffic management, monitoring and analysis

Feature	Description					
<b>IPv4 and IPv6 dual stack</b>	Coexistence of both protocol stacks to migration					
<b>Firmware upgrade</b>	<ul style="list-style-type: none"> <li>• Web browser upgrade (HTTP/HTTPS) and TFTP</li> <li>• Upgrade through console port as well</li> <li>• RubyView to deploy the switch firmware</li> </ul>					
<b>Port mirroring</b>	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe. Up to 8 source ports can be mirrored to single destination port. A single session is supported.					
<b>Easy-Port-Configuration</b>	Easily to configure of clients' QoS and Security capabilities.					
<b>USB Memory</b>	Firmware upgrade and configuration backup and restore <b>(Option)</b>					
<b>Watchdog</b>	When CPU hangs due to some fault condition, the watchdog timer will reset the switch					
<b>Alarm Notification</b>	Use diagnostic LED and buzzer to do abnormal events indication					
<b>HW Monitoring</b>	Monitor working voltage and temperature to detect abnormal status and issue alarm					
<b>Other management</b>	Single IP management; HTTP/HTTPS; SSH; RADIUS; DHCP Client; SNMP; cable diagnostics; ping; syslog; Telnet client (SSH secure support)					
<b>s-Flow</b>	The industry standard technology for monitoring high speed switched networks. It gives complete visibility into the use of networks enabling performance optimization, accounting/billing for usage, and defense against security threats					
<b>Green Ethernet</b>						
<b>Link detection</b>	Compliant with IEEE 802.3az Energy Efficient Ethernet Task Force. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or idle of client. Active mode is resumed without loss of any packets when the switch detects the link up					
<b>Cable length detection</b>	Adjusts the signal strength based on the cable length. Reduces the power consumption for cables shorter.					
<b>General</b>						
<b>Jumbo frames</b>	Frame sizes up to 9KB supported on Gigabit interfaces					
<b>MAC Table</b>	Up to 8K MAC addresses.					
<b>Discovery</b>						
<b>Link Layer (LLDP) Discovery Protocol (IEEE 802.1AB) with LLDP-MED extensions</b>	Used by network devices for advertising their identity, capabilities, and neighbors on a IEEE 802 local area network, principally wired Ethernet.					
<b>Power over Ethernet (PoE)</b>						
<b>IEEE 802.3at PoE delivered over each of the RJ-45 ports within the listed power budgets</b>	<b>Model Name</b>	<b>IEEE 802.3at</b>	<b>IEEE 802.3af</b>	<b>Power Dedicated to PoE</b>		
	PSGS-2612	Port 1-8	Port 1-8	130W/185W <b>(Optional)</b>		
<b>Interface</b>						
<b>Ports</b>	<b>Model Name</b>	<b>Total System Ports</b>	<b>RJ-45 PoE Ports</b>	<b>RJ-45 Ports</b>	<b>(100/1G) SFP</b>	<b>Option Module</b>
	PSGS-2612	12	8	2	2	--
<b>Environmental (preliminary)</b>						
<b>Dimensions</b>	280(W) x 44(H) x 210(D)					
<b>Weight (kg)</b>	Kg					
<b>Power</b>	100-240 VAC 50~60 Hz, internal, universal					
<b>Certification</b>	CE Mark, FCC Part 15 (CFR47) Class A					
<b>Operating temperature</b>	0 to 40°C					
<b>Storage temperature</b>	-20°C to 70°C					
<b>Operating humidity</b>	10% to 90%, relative, noncondensing					

Feature	Description
<b>Package Contents</b>	
<ul style="list-style-type: none"> <li>• Switch</li> <li>• Power Cord</li> <li>• Mounting Kit (Option)</li> <li>• Console Cable</li> <li>• CD-ROM with user manual documentation (PDF) included</li> <li>• QIG (Quick Install Guide)</li> </ul>	
<b>Minimum Requirements</b>	
<ul style="list-style-type: none"> <li>• Web browser: Mozilla Firefox version 2.5 or later, Microsoft Internet Explorer version 6 or later</li> <li>• Category 5 Ethernet network cable</li> <li>• TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in network</li> </ul>	

### Ordering Information

Model Name	Description
<b>PSGS-2612.130</b>	8-Port GbE UTP with PoE + 2-Port GbE UTP without PoE + 2-Port (100/1G) SFPL2 Plus Managed Switch (PoE: 130W)
<b>PSGS-2612.185</b>	8-Port GbE UTP with PoE + 2-Port GbE UTP without PoE + 2-Port (100/1G) SFPL2 Plus Managed Switch (PoE: 185W)
<b>USB-26</b>	USB Flash with Key-Lock function

**Ruby Tech Corp.**

 3F, No.1, Lane 50, Nan Kang Road, Sec.3, Taipei, Taiwan  
 TEL:886-2-2785-3961 FAX:886-2-2786-3012

<http://www.rubytech.com.tw>

 E-mail : [rubytech@mail.rubytech.com.tw](mailto:rubytech@mail.rubytech.com.tw)