

BPC



SE-8210

High Performance Fanless Embedded PC

Features and Benefits:

- Intel® Core 3rd Gen. mobile i3/i5/i7 (rPGA-988) processor
- Intel® QM77 / HM76 chipset
- 4 x USB 3.0
- Built-in CFast slot for external storage or system boot up
- Riser card support 1x PCIe x4
- Optional 802.11b/g/n Wi-Fi Module
- Three Independent display supported
- Support 9~36V wide range DC-in



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714-996-7200 FAX: +1-714-996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.

OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>




ISO CERTIFIED
9001 14001


SE-8210

High Performance Fanless Embedded PC



Rear View



Side View



Front View



Unit: mm

Specification

System	
CPU Support	Intel® mobile i3 / i5 / i7 (rPGA-988) processor
Chipset	Intel® QM77 / HM76
Memory Support	2 x 204Pin DDR3 So-DIMM, Support DDR3/DDR3L 1600/1333/1066 up to 8GB/slot
Watchdog	1~255 secs Watchdog timer selectable w / Reset / NMI
Driver Bay	2.5" SATA HDD drive bay x 1 Slim DVD-ROM X1(option)
Audio	High Definition Audio; 1 x Line-out / 1 x Mic-in
Power Supply	9~36V DC-in
Expansion Slot	1 x mini PCI-E slot (for WLAN module & 3G module) 1 x SIM card slot 1 x CFAST slot 1 x PCIe x4: 10W max./slot(option) (DVD-ROM / PCIe-expansion either)
Operating System	Microsoft Windows XP, Win7
Dimension (W x H x D)	260mm(W) x 89mm(H) x 200mm(D) (10.24" x 3.5" x 7.87")
Certificate	FCC / CE

I/O Ports (Front side)

Serial Port	2 ports support (COM 5/6 for RS232 only)
Digital I/O	DSUB-25, 8in/8out or Phoenix-16p (option)
USB	2 x USB2.0
Parallel port	1 x DSUB-25
Display port	2 x
SIM card / CFAST slot	1 x / 1x

I/O Ports (Rear side)

Serial Port	4 ports support (COM1/3/4 for RS232, COM2 for RS232/422/485, pin-9 5V/12V/RI selectable)
VGA	1 x VGA
LAN	LAN1 : Intel® 82579LM 10/100/1000 LAN LAN2 : Intel® 82583V 10/100/1000 LAN Support wake-on-LAN
Audio	1 x Line out, 1 x Mic-in
USB	4 x USB3.0
DC-IN	1 x 9~36V (DIN type 4 pin connector)

Environment

Operation Temp.	HDD:-5°C ~45°C
Ambient with air flow	CFAST card (Wide-Temp grade):-5°C ~ 55°C (w/o Audio)
Storage Temp.	- 20°C ~ 80°C
Humidity	10% ~ 90%

Ordering Information

SE-8210RA-A0B	Intel® QM77 barebone Embedded PC with DSUB-25 DIO
SE-8210RA-B0B	Intel® QM77 barebone Embedded PC with Phoenix-16p DIO
SE-8210RA-C0B	Intel® HM76 barebone Embedded PC with DSUB-25 DIO
SE-8210RA-D0B	Intel® HM76 barebone Embedded PC with Phoenix-16p DIO

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Dec. 2012.