

CVT-3002-PLUS-DR Series Media Converter



Gigabit Ethernet 10/100/1000Base-T to
100/1000Base-X Media Converter

Features

- **The World-wide Effortless and Reliable Media Converter**
The almost “set-it-and-forget-it” media converter is for minimizing network implementation and maintenance efforts
- **9K Bytes Jumbo Frame Size**
Support jumbo frame size 9K bytes to ease the network traffic loading and facilitate IPTV service
- **Link Alarm**
When UTP or fiber port is down during operation, the other port will be automatically turned off to alert the user
- **Fully Compatible with CVT-RACK-16**
Budget limited solution for CVT-RACK-16 to mix installation with CTS’s non-managed converter
- **Dual Rate**
Dual Rate media converter with auto-sensing function can automatically adjust to the speed of the slide-in fiber transceiver. This can save the cost when upgrading the device from 100Mbps to 1000Mbps

Target Applications

- **FTTX implementations. Point-to-point fiber connection for long distance**


Description

Connection Technology Systems (CTS) CVT-3002-PLUS-DR series media converter are the Gigabit Ethernet 10/100/1000 Base-T to 100/1000Base-X media converter. The CVT-3002-PLUS-DR series media converter converts traditional twisted-pair RJ-45 cable into various fiber media including multi-mode, single-mode, SC connector, bi-directional WDM, or a SFP slot for pluggable fiber transceiver. The traditional transmission distance of 100m over RJ-45 copper can be extended from 550m to 80km over fiber.

CVT-3002-PLUS-DR series media converter is fully compliant with IEEE 802.3, 802.3u, 802.3ab & 802.3z standards. Besides, it is equipped with some switching features including flow control and store and forward.

The installation and operation are simple and straightforward. The operation status can be monitored through a set of diagnostic LED indicators on the front panel. It is especially designed for network operators, metro Ethernet providers, enterprises, SMB, who have the need of implementing fiber optical Ethernet networks over long distance, for FTTX solutions, and are looking for an effortless and reliable 1000Mbps media converter.

Application Diagram



Specification

Interface

TP Port
10/100/1000Base-T RJ-45 x 1
F/O Port
100/1000Base-X x 1

Standards

IEEE 802.3 10Base-T
IEEE 802.3u 100Base-TX/FX
IEEE 802.3ab 1000Base-T
IEEE 802.3z 1000Base-X
IEEE 802.3x Flow Control

H/W Specification

Auto-Negotiation in TX port
MDI/MDIX Auto-Crossover supported
Support Auto & Force mode configuration
1K MAC Address Table
32K Memory Buffer

LED

Power, FDX, Status, Speed,
F/O Link/Act, TX Link/Act

Ethernet Features

Support 9K Bytes jumbo frame
Support Flow Control
Store and Forward Switching Mechanism

Other Features

Rear Panel DIP Switch
Support Link Alarm
Support slide-in Converter Center

Power Requirement

Power adaptor
- AC input: 100VAC~240VAC
- Frequency range: 50~60Hz
- DC output: 5V, 2.0A
Power Consumption: 2.2W

Environmental Condition

Operation: 0°C ~ 50°C
Storage Temperature: -20°C ~ 60°C
Humidity: 5% ~ 90%, non-condensing

Dimension & Weight

Size: 71 x 94 x 26 mm (WxDxH)
Shipping Weight: 0.6KG

EMC/Safety

FCC Class A, CE
* For further reports, please contact us for update

Order Information

CVT-3002-PLUS-DR Series

MODEL	FIBER PORT					TP PORT	
	Speed	Fiber Type	Connector	Distance	Ports	Speed	Ports
CVT-3002BTFC(SM-10)-PLUS-DR	100/1000	SM	SC	10KM	1	10/100/1000	1
CVT-3002W2A(SM-10)-PLUS-DR	100/1000	WDM	SC	10KM	1	10/100/1000	1
CVT-3002W2B(SM-10)-PLUS-DR	100/1000	WDM	SC	10KM	1	10/100/1000	1
CVT-3002SFP-PLUS-DR	100/1000	SFP	-	-	1	10/100/1000	1

SFP-31-DR Series

MODEL	FIBER PORT				
	Speed	Type	Connector	Distance	Wavelength
SFP-31FC-DR	100Mbps/1000Mbps	MM	LC	550M/2KM	1310nm
SFP-31FC(SM-10)-DR	100Mbps/1000Mbps	SM	LC	10KM	1310nm
SFP-31W2A(SM-10)-DR	100Mbps/1000Mbps	WDM	LC	10KM	TX:1310nm RX:1550nm
SFP-31W2B(SM-10)-DR	100Mbps/1000Mbps	WDM	LC	10KM	TX:1550nm RX:1310nm

SFP-31 Series

MODEL	FIBER PORT				
	Speed	Type	Connector	Distance	Wavelength
SFP-31FC	1000Mbps	MM	LC	550M	850nm
SFP-31FC(SM-10/20/40/50/80/120)	1000Mbps	SM	LC	10/20/40/50/80/120KM	1310nm/1310nm/1310nm/1550nm/1550nm/1550nm
SFP-31W2A(SM-10/20/40/80)	1000Mbps	WDM	LC	10/20/40/80KM	TX:1310nm/1310nm/1310nm/1490nm RX:1550nm/1550nm/1550nm/1570nm
SFP-31W2B(SM-10/20/40/80)	1000Mbps	WDM	LC	10/20/40/80KM	TX:1550nm/1550nm/1550nm/1570nm RX:1310nm/1310nm/1310nm/1490nm
SFP-31FC-C09	1000Mbps	CWDM	LC	80KM	1430nm
SFP-31FC-C10	1000Mbps	CWDM	LC	80KM	1450nm
SFP-31FC-C11	1000Mbps	CWDM	LC	80KM	1470nm
SFP-31FC-C12	1000Mbps	CWDM	LC	80KM	1490nm
SFP-31FC-C13	1000Mbps	CWDM	LC	80KM	1510nm
SFP-31FC-C14	1000Mbps	CWDM	LC	80KM	1530nm
SFP-31FC-C15	1000Mbps	CWDM	LC	80KM	1550nm
SFP-31FC-C16	1000Mbps	CWDM	LC	80KM	1570nm
SFP-31FC-C17	1000Mbps	CWDM	LC	80KM	1590nm
SFP-31FC-C18	1000Mbps	CWDM	LC	80KM	1610nm

SFP-21 Series

MODEL	FIBER PORT				
	Speed	Type	Connector	Distance	Wavelength
SFP-21FC	100Mbps	MM	LC	2KM	1310nm
SFP-21FC(SM-20/40/80)	100Mbps	SM	LC	20/40/80KM	1310nm/1310nm/1550nm
SFP-21W2A(SM-20/40/80)	100Mbps	WDM	LC	20/40/80KM	TX:1310nm/1310nm/1490nm RX:1510nm/1510nm/1570nm
SFP-21W2B(SM-20/40/80)	100Mbps	WDM	LC	20/40/80KM	TX:1510nm/1510nm/1570nm RX:1310nm/1310nm/1490nm
SFP-21W2A(SM-20)SC	100Mbps	WDM	SC	20KM	TX:1310nm RX:1550nm
SFP-21W2B(SM-20)SC	100Mbps	WDM	SC	20KM	TX:1550nm RX:1310nm
SFP-21FC-C09	100Mbps	CWDM	LC	80KM	1430nm
SFP-21FC-C10	100Mbps	CWDM	LC	80KM	1450nm
SFP-21FC-C11	100Mbps	CWDM	LC	80KM	1470nm
SFP-21FC-C12	100Mbps	CWDM	LC	80KM	1490nm
SFP-21FC-C13	100Mbps	CWDM	LC	80KM	1510nm
SFP-21FC-C14	100Mbps	CWDM	LC	80KM	1530nm
SFP-21FC-C15	100Mbps	CWDM	LC	80KM	1550nm
SFP-21FC-C16	100Mbps	CWDM	LC	80KM	1570nm
SFP-21FC-C17	100Mbps	CWDM	LC	80KM	1590nm
SFP-21FC-C18	100Mbps	CWDM	LC	80KM	1610nm