

## ARC-8008-SAS/Fibre/iSCSI

### External SAS RAID Controller (Backplane Solution)

#### SAS for Maximum Scalability

The 12Gb/s SAS interface supports both 12Gb/s SAS disk drives for data-intensive applications and 6Gb/s SATA drives for low-cost bulk storage of reference data. The Fibre/SAS/iSCSI to 12Gb/s SAS RAID controllers attach directly to SATA/SAS midplanes with 3/4 x Z-PACK HM-Zd high speed connectors or increase capacity using one additional Min SAS HD SFF-8644 external connector. The ARC-8008 supports flexibility interface configuration; 8 x 12Gb/s SAS ports, 2/4 x 16Gb/s fibre channels or 2 x 10Gb/s iSCSI channel host and 4 x 12Gb/s SAS ports expander for performance and easy expansion. When used with 12Gb/s SAS expanders, the controller can provide up to (256) devices through one or more SAS JBODs, making it an ideal solution for enterprise class storage applications that called for maximum configuration flexibility. The Fibre/SAS/iSCSI to 12Gb/s SAS cable solution RAID controller provides a rack-mounted external storage chassis capable of accommodating up to 12/16/24 12.0-Gb/s, Serial-Attached SCSI (SAS) drives or 6.0-Gb/s Serial ATA (SATA) drives. It provides three kinds of host interface link to the host board on the server system. The redundant controller model provides fault-tolerant links across separate host interface, while the single controller model provides a single, straight-through data path.

#### Unsurpassed Data Availability

Designed and leveraged with Areca's existing high performance RAID solution, ARC-1883 provides superior levels performance and enterprise level data protection for the most demanding next generation server and storage environments. It supports the hardware RAID 6 engine to allow two HDDs failures without impact the existing data and performance. It allows users to hot swap drive in the event of a drive failure with zero downtime. With innovative new RAID-on-Chip 12Gb/s SAS feature and support for SATA, SAS and SSDs, the SAS RAID subsystems provides small- to mid-sized enterprises with superior levels of RAID performance and scalability for external storage. The optional flash-based backup module (FBM) provides power to transfer the cache data from the SDRAM memory to the NAND flash memory if it contains data not yet written to the drives when power is lost. The subsystem also supports traditional Lithium-ion (Li-ion) battery backup module (BBM) to protect cached data on RAID adapters.

#### Unparalleled Performance for 12Gb/s SAS

The 12Gb/s SAS RAID subsystems raise the standard to higher performance levels with several enhancements including new high performance 1.2 GHz dual core ROC processor, a DDR3-1866 memory architecture and high performance PCIe 3.0 interface bus interconnection. The subsystem each includes one 240-pin DIMM socket with default 2GB DDR3-1866, single rank, 1Rx8, upgrade to 8GB or 8GB DDR3-1600, dual rank, 2Rx8, ECC SDRAM. The 12Gb/s SAS is designed for backward compatibility with 6Gb/s and 3Gb/s SAS and SATA hard drives. Regardless of the drive speed, 12Gb/s SAS RAID controllers will provide maximum read/write performance improvements for the most performance-hungry database and IT applications. The subsystem includes one 12Gb/s SAS expander that incorporates the latest enhancements in SAS along with new LSI DataBolt bandwidth optimizer technology. This is designed to help facilitate the industry transition to 12Gb/s SAS-enabled systems by allowing users to take advantage of 12Gb/s speeds while utilizing existing 6Gb/s drives and backplanes. Using DataBolt, the subsystem buffers 6Gb/s data and then transfers it out to the host at 12Gb/s speeds in order to match the bandwidth between faster hosts and slower SAS or SATA devices.

#### Easy RAID Management

Configuration and monitoring can be managed either through the LCD control panel, RS232 port or LAN port. The firmware also contains an embedded terminal emulation via the RS-232 port. The firmware-embedded web browser-based RAID manager allows local or remote to access it from any standard internet browser via a LAN port. The controller also supports API library for customer to write its own monitor utility. The Single Admin Portal (SAP) monitor utility can support one application to manage multiple RAID units in the network.

## Controller Architecture

- Dual core RAID-on-Chip (ROC) 1.2GHz processor
- One 240-pin DIMM socket for 2GB (default) DDR3-1866, 1RX8, ECC module
  - up to 4GB or 8GB DDR3-1866, 1RX8, Unbuffered/Registered ECC module or
  - up to 4GB or 8GB DDR3-1600, 2RX8, Unbuffered/Registered ECC module
- Write-through or write-back cache support
- Supports up to 256 SATA or SAS devices using SAS expanders
- DataBolt™ Bandwidth Optimizer for balance faster host and slower SAS or SATA devices.
- Redundant flash image for controller availability
- Real time clock support
- Support flash-based or battery backup module (FBM/BBM) ready (optional)

## RAID Feature

- RAID level 0, 1, 10(1E), 3, 5, 6, 30, 50, 60, Single Disk or JBOD
- Multiple RAID 0 and RAID 10(1E) support (RAID 00 and RAID100)
- Multiple RAID selection
- Configurable stripe size up to 1024KB
- Support HDD firmware update
- Online array roaming
- Online RAID level/stripe size migration
- Online capacity expansion and RAID level migration simultaneously
- Online volume set growth
- Instant availability and background initialization
- Support global and dedicated hot spare
- Automatic drive insertion/removal detection and rebuilding
- Support for native 4K and 512 byte sector SAS and SATA devices
- Multiple pairs SSD/HDD disk clone function
- SSD automatic monitor clone (AMC) support
- Support intelligent power management to save energy and extend service life
- Support NTP protocol to synchronize RAID controller clock over the on-board LAN port
- Redundant controller operation with active/active and failover/failback function
- Dual-active RAID controller with cache mirroring through dedicated high speed bus
- Automatic synchronization of firmware version in the dual-active mode
- Multi-path & load-balancing support (MPIO)
- Max 256 devices
- Max 128 LUNs (volume set) per controller
- Management port seamless take-over

## Host Interface

- **SAS-to-SAS**  
Two 12Gb/s SAS Ports
- **Fibre-to-SAS**  
Two or Four 16Gb/s Fibre channels
- **iSCSI-to-SAS**  
Two 10Gb/s iSCSI channels
  - iSCSI Hardware iSCSI off-load engine
  - iSCSI jumbo frame
  - iSCSI Header/Data digest support
  - iSCSI CHAP authentication

## Software Drivers

- OS Independent

## Monitors/Notification

- LCD control panel for setup, alarm mute and configuration
- System status indication through LCD, LED and alarm buzzer
- SMTP support for email notification
- SNMP support for remote manager
- Enclosure management ready

## RAID Management

- Field-upgradeable firmware in flash ROM
- Firmware-embedded manager via RS-232 port
- Firmware-embedded web browser-based RAID manager access your RAID subsystem from any standard internet browser via a LAN port
- Access terminal menu by telnet via a LAN port
- API library for customer to write its own monitor utility
- SAP management utility to easily manage multiple RAID unit in the network

## Drive Interface

- Up to 24 x 12Gb/s internal port
- 1 x SAS "Expansion Out" Min SAS HD SFF-8644 connector for an additional JBOD enclosure
- Up to 256 12Gb/s SAS or 6Gb/s and 3Gb/s SAS/SATA HDDs/SSD, using 12Gb/s SAS Expander

## Environment

- Temperature:  
Operating: 0° to 40°C / Storage: -40° to 60°C
- Relative humidity:
  - Operating 10% to 80% (non-condensing)
  - Storage 5% to 95% (non-condensing)

## Electrical

- Power Requirements : 37.2W max. on +12V

Model Name	ARC-8008-2S	ARC-8008-2F/4F	ARC-8008-2I
I/O Processor	Dual core RAID-on-Chip (ROC) 1.2GHz		
Host Bus	2 x 4 lanes 12Gbps SAS	2/4 x 16Gbps Fibre	2 x 10Gbps Ethernet
Host Connector	2 x SFF-8644	2/4 x SFP	2 x SFP+
Drive Connector	3/4 x (2 pair 10 columns) Z-Pack HM-Zd connectors + 1 x External SFF-8644 Connector for expander		
Management Interface	2 x RJ11: Serial Port, 1 x RJ45: Ethernet Port		
Form Factor	146 (W) x 43 (H) x 250 (L)		



8F., No.22, Lane 35, Ji-Hu Rd., 114 Taipei, Taiwan, R.O.C.  
TEL: 886-2-87974060 FAX: 886-2-87975970  
http://www.areca.com.tw  
Technical Support: support@areca.com.tw  
Sales Information: sales@areca.com.tw



Areca is a registered trademark of Areca Technology Corporation. Other brand names and product names are trademark or registered trademarks of their respective companies. This specification may be changed at any time without prior notice.