



## Mini Fixed-mount barcode scanner

### Features

- High-quality Mini Fixed-mount CCD barcode scanner.
- It supports USB HID interface or USB Serial interface.
  - \*\* USB HID: Plug & Play, No extra driver is needed.
  - \*\* USB Serial: can send command to scanner, data will be sent to COM port.
- Small-size, Lightweight, designed for easy operation & installation
- Suitable for ATM, KIOSK, Price Checker, and other fields.

### Specifications :

Model Name	<b>FS5107A</b>
Engine	Ultra-long range CCD scan engine

### Performance Characteristics

• Light source	610nm~640nm Red LED
• Depth of field ( There are +/- 1 cm tolerance )	Code 39 ( 5mil): 65mm ~ 175mm EAN-13 (13mil): 55mm ~ 605mm
• Scan speed	300 scans/sec
• Best resolution	4 mil
• Scan Angle	Pitch $\pm 60^\circ$ @ $0^\circ$ Roll and $0^\circ$ Skew Roll $\pm 30^\circ$ @ Pitch and $0^\circ$ Skew Skew $\pm 60^\circ$ @ Roll and $0^\circ$ Pitch
• Interface	Micro USB cable ( USB HID ,USB Serial <by request> )
• Print contrast	$\geq 30\%$
• Symbologies	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, Interleaved 2 of 5, ITF-6, ITF-14, Industrial 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI

### Electrical Characteristics

• Input voltage	5 V/DC (from Smartphone / Tablet Power)
• Current - operating	85 mA max

### Physical Characteristics

• Dimension (L * W * H)	43 X 34 X 16 mm (without cable)
• Color of housing	Black
• Weight	26 g

### Environment

• Temperature-operation	$0^\circ\text{C}$ to $50^\circ\text{C}$
• Temperature-storage	$-10^\circ\text{C}$ to $60^\circ\text{C}$
• Humidity-operation	5% to 95% relative humidity, non-condensing

*Product specification is subject to change without notice.*

**RIOTEC CO., LTD.**

**8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan**

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw