



CHAM. 30° TO MAX.
DIA. ACROSS FLATS.
(倒角 30° 至對邊平面之最大尺寸位置)

NOTES: MATERIAL & FINISH
 1. BRASS C3604B
 2. PHOSPHOR BRONZE C5441B
 3. Cu0.76um MIN. Ni2.54um MIN.
 4. Cu0.76um MIN. Ni2.54um MIN. Au FLASH

- 1. CRIMPED FERRULE
HEX. CRIMP SIZE .105"
- 2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
7	INSULATOR	PTFE	NATURAL	1	
6	BODY	NOTE1	NOTE3	1	
5	SHELL	NOTE1	NOTE3	1	
4	RETAINING RING	NOTE2	NOTE3	1	
3	CONTACT	NOTE2	NOTE4	1	
2	INSULATOR	PTFE	NATURAL	1	
1	BODY	NOTE1	NOTE3	1	

Seconn International Enterprise Co., Ltd.

TOLERANCES		PROJECTION	TITLE				
ABOVE 315 mm	± 1.60		FME STR plug to SMB plug adapter				
120 - 315 mm	± 1.00						
40 - 120 mm	± 0.60						
06 - 40 mm	± 0.20						
UP To 06 mm	± 0.12						
Angle	± 3°	UNIT					
		mm					
DRAWN	Bob	DATE	2011/12/06	PART NO.	SC-S-24F10F001F		
SCALE	6:1	SIZE	A4	SHEET	1/1	REV	A0