

U2485DB-I

Universal RS232 or RS422/RS485 to

Ground Isolated RS232 or RS422/485 Isolator & Converter.

Double barrier Isolated feature

Input, Output and Power **triple isolated feature** to break Ground loop



- ★ Port A(RS232) to Port B(RS232) GROUND isolator.
- ★ Port A(RS232) to Port C(RS422/RS485) interface converter.
- ★ Port D(RS422/RS485) to Port C(RS422/RS485) repeater or Bridge.
- ★ Double Barrier Isolated Feature between input and output connector.
- ★ Triple way Isolation to break any Ground loop and stray current.
- ★ Full-duplex RS422 or Half-Duplex RS485 interface set by DIP switch
- ★ Each connector with data transmission LED indicator

U2485DB-I specifications :

RS232 interface :

- ◆ Connector type : DB9 male connector.
- ◆ Number of ports : 2

NOTE : port A is RS232 input to work with Port D.

NOTE : port B is RS232 output to work with port C..

Interface type setting :

- ◆ Use one 4 bit DIP switch to set for RS422 (ON) or RS485 (OFF) interface. Bit 1 is for port A(no use here), bit 2 for port B(no use here), bit 3 for port C, bit4 for port D.

Power input :

- *UP110/UP220 US/EU type power adaptor
- *100--240 VAC input.
- *5VDC 1000mA output.
- *Current consumption: 400mA @ 5VDC.

Environment :

- ◆ operating temperature : 0°C to 55°C .
- ◆ operating humidity : 0% to 95% RH.
- ◆ storage temperature : 0°C to 65°C .
- ◆ storage humidity : 5% to 95% RH.

RS422/485 interface :

- ◆ Connector type : DB9 male connector.
- ◆ Number of ports : 2

Note: port D is input to work with port A.

Note: port C is output to work with port B.

NOTE : RS422 or RS485 interface type set by DIP switch.

NOTE : each port with isolated signal ground.

NOTE : each port with 5 signal pin TX+ , TX- , RX+ , RX- , isolated GND.

NOTE : In RS485 interface type support

Auto-Data-Direction-Control feature. Pin 2 and pin3 is shorted as Data+ signal. Pin4 and pin6 is shorted as Data- signal. Can work with TB485 module to exchange DB9 to 3pin terminal block.

LED indicator :


- ◆ Power : DC power input ON indicator.
- ◆ AT/RX : RS232 port A TX/RX signal activity.
- ◆ BT/RX : RS232 port B TX/RX signal activity.
- ◆ CT/RX : RS485 port C TX/RX signal activity.
- ◆ DT/RX : RS485 port D TX/RX signal activity.

Dimension :

- ◆ U2485DB-I box :
90mm (W) * 150mm (L) * 27mm(H)

Accessories :

TB485 : DB9 Female to RS485 terminal block kit.



Performance upgrade capability and relative products.

- ▲ UCON301-I box : one port RS232/RS422/RS485 to ground isolated RS422/485 converter.
- ▲ UCON232DB-I box : Triple way Ground isolated RS232 to RS232 isolator.
- ▲ UCON422DB-I box : Triple way Ground isolated RS422/485 to RS422/RS485 repeater & Bridge.
- ▲ UCON485DB-I box : Triple way Ground isolated RS232 to RS422/RS485 Interface converter.
- ▲ RS4232-4 box : 4 RS232 to Ground isolated RS232/422/485 converter box.
- ▲ RS4232-8 box : 8 RS232 to Ground isolated RS422/485 converter box.

©All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou , New Taipei city, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@msl.hinet.net, info@rayontech.com.tw

WEB: <http://www.rayontech.com.tw>