



Card Reader

Card Reader eSATAp > Compact Flash

Description

This Delock Card Reader can be connected to a Power Over eSATA port, a combination of eSATA and USB. It enables reading and writing of Compact Flash memory cards.

You have two different connecting options:

1. Power Over eSATA Port
2. eSATA Port + USB Port for power supply

Images



Ref.	91689
EAN	4043619916894
Country of origin	Taiwan
Customs tariff number	84719000

Specification

- Aluminium case
- Interface:
 - 1 x Power Over eSATA (eSATAp) 5 V,
 - 1 x DC jack for power supply via an USB port
(only required when using the eSATA interface)
 - 1 x CF card slot
- Supports Compact Flash cards type I / II, Extreme IV and Micro Drive memory cards
- Supports CF cards with PIO, DMA and UDMA mode
- Data transfer rate up to 1.5 Gb/s
- Dimension (LxWxH): 67 mm x 60 mm x 12 mm
- Hot Swap, Plug & Play

System requirements

- Windows 2000/XP/Server-2003/Vista/7, Mac OS 10.x or above, Linux
- PC or notebook with one free eSATAp port or one free eSATA and one free USB port

Package content

- Card Reader eSATAp to CF
- eSATAp cable
- USB power cable
- User manual

Package

- Box