



PACKING: 10 PCS / Bundle

Pin Assignments

P1 DB9	1	2	3	4	5	6	7	8	9	/
P2 IDC	1	2	3	4	5	6	7	8	9	/
COLOR	RED			GREY						

- ELECTRONIC TEST CONDITION:
1. 100% OPEN SHORT & MISWIRE TEST.
 2. CONDUCTION RESISTANCE: 2Ω/MAX.
 3. INSULATION RESISTANCE: 20MΩ/MIN. AT DC 300V.

PART LIST: ALL "ROHS" COMPLIANT, ALL MATERIALS ARE EQUIVALENT.

4	IDC 10P PH:2.54 3 PARTS COLOR:BLACK	1	SET
3	HEX COLUMNS 4.75*4.8*11.7 4#40.	2	PCS
2	DB9P MALE SOLDER TYPE · BLUE PBT INSULATOR, LONG EAR +DKEN QUICKLY ASSEMBLY SHELL .	1	PCS
1	UL2651 28AWG*9C PH:1.27MM GREY ROW RED EDGE, L=285MM	1	PCS
ITEM	STANDARD SPECIFICATION	Q' TY	UNIT

Seconn International Enterprise Co., Ltd.

TOLERANCES		PROJECTION	TITLE	
AS DRAWING			D-SUB 9P MALE TO IDC 2.54MM 10P FLAT GREY CABLE	
		UNIT mm		
DRAWN	DIANA	DATE	PART NO.	SC-S-1808-0401
SCALE		SIZE	SHEET	1/1 REV A