



Model Name:KVM3322/KVM3324

2/4 Ports USB to USB KVM Switch w/ Audio and USB Hub

Features

- Compliant with USB1.1 specification
- Built-in Audio ports for PC sharing
- Built-in USB 1.1 Hub for sharing USB devices
- Supports VGA, SVGA, XGA and multi-sync monitors, resolution upto 1920 x 1440
- Supports bus-power or self-power with optional power adapter (optional power adapter is not included)
- Supports 4 different modes of key sequence to let users to switch among four PC easily using hot key defined on left side of keyboard
- Support Win98SE/2000/ME/XP/Vista, Mac, Linux
- Hot Swappable – Add/Remove PCs without turn-off the KVM switch and/or PCs
- LED display and auto-scan mode for status monitoring
- Buzzer sound for switching port confirmation
- Open-Box-Ready with completed cable sets for users' convenience
- No Software Required - easy PC selection via Push Buttons / Hot key

Specifications

Model #	KVM3324	KVM3322
Console Port	1	1
Max PC Connection	4	2
PC Port Selection	Push Button / Hot key	Push Button / Hot key
LED	4	4
Cable	4*1.5M	2*1.5M
Computer Port (All Female Type)		
Keyboard, Mouse, Video	4*HDDDB 15 pin (VGA)	2*HDDDB 15 pin (VGA)
Speaker	4*Mini Stereo Jack	2*Mini Stereo Jack
Microphone	4*Mini Stereo Jack	2*Mini Stereo Jack
Console Port (All Female Type)		
Monitor	1*HDDDB 15 pin (VGA)	1*HDDDB 15 pin (VGA)
Keyboard	1*Type A USB	1*Type A USB
Mouse	1*Type A USB	1*Type A USB
Speaker	1*Mini Stereo Jack	1*Mini Stereo Jack
Microphone	1*Mini Stereo Jack	1*Mini Stereo Jack
USB Hub	1*Type A USB	1*Type A USB
Power		
Bus-powered	PC power	
Self-powered	Optional DC5V 1A Adapter (not included)	
Resolution	Upto 1920 x 1440	
AutoScan Interval	5~60 seconds (10 seconds default)	
Physical Dimension	218mm x 77.8mm x 37.7mm or 8.6in x 3.1in x 1.5in (Plastic housing)	
Support OS	Win98SE/2000/ME/XP/Vista, Mac, Linux	