



### Spec synopsis

This 65" touch monitor is integrated with infrared touch technology to help enhance presentation experience as well as any large audience-based seminar, speech purpose. With direct-view LCD at adequate brightness, this 65" touch monitor shows clear sharp FHD picture and color for text and graphics, or video footage. No long will shadows be created by presenter/speaker himself due to projection, and with full emulation of mouse function, assistants are not required to aid the presenter, no more yelling "next page", presenter is in full control of his own presentation. In summary, this 65" touch monitor is a combination of white board and projection interactive whiteboards which serves and maximize your investment.

## 65"LCD Touch Monitor Model:GT65MAZ

Panel size(diag.)	65 inch
Native resolution	1920 x 1080
Max. display mode	1920X1200/60Hz
Brightness	450 nits
Contrast	2000:1
View angle	176° / 176°
Response time	6ms
Backlight life	60,000 hours
Operating temp.	0-50 degree C
Operating humid.	20 – 100 % RH
Input Voltage	AC100~240V 50/60 Hz
Power Consump.	<550 watts
Standby power	<3 watts
Input connector	VGA x1 , DVIx1
Output connector	VGAx1
Screen control	RS-485 & remote handset
Ambient detection	Auto ambient light detection
Weight	<85 kg.
Dimensions(WxHxD)	1561 x 920 x 143 mm
Protective glass	4mm
Touch panel	Infrared