



CARE . TRUST . RESPONSIBILITY

EM-300
10.1"
Windows
Enterprise
Tablet



Bring mobility into your business
EM-300 Special Features

- Innovation design brings revolution to POS system
- Compact, slim and light weight design
- Portrait or landscape display
- Power vining design for maximum battery life
- Wireless communication capabilities
- Ruggedized and IP54 design
- Variable and flexible functions with peripherals and accessories

Optional

- POS base
- Charging cradle
- 1D/2D barcode reader
- 3-track MSR
- IC card reader
- Fingerprint reader

EM-300 Enterprise Tablet

The goal of any automation plan is to improve profitability, and EM-300 enables you to accomplish this goal by reducing errors, improving customer satisfaction, and increasing sales. Additionally, it allows your in-store and on-the-road personnel to reach higher levels of productivity, as less time is spent on traditional data search and entry.

Partner Tech's EM-300 enterprise tablet is a state of the art mobile terminal with multiple functions, and the modern yet smart design that fits into various applications in fields, such as logistics, retail and hospitality. EM-300 brings advance performance to your business at the touch of your fingers.

Item	EM-300
Processor	Intel® Processor Braswell N3000
OS	Windows Industry 8.1 Pro Retail, Win 10 IoT for Tablets
Memory/Storage	2G/32G; 4G/64G
Display	10.1", 1280 x 800, 350nits
Touch	Projected capacitive touch (Multi Touch)
Bluetooth	V4.0+HS
WiFi	802.11 a/b/g/n
WWAN(option)	For data, GPRS/EDGE/WCDMA/850/900/1800/1900/2100
GPS(option)	Stand Alone & AGPS (Support Glonass), E-compass included
Sensor	G-sensor
Battery	Rechargeable Li-ion battery 7.4V, 4000mAh
Working time	5 hours@film with speaker, 50% brightness, WiFi on
Speaker	Internal, 2*0.8W
I/O	1* SIM (internal) 1* DC Jack 1* Earphone & MIC Jack 1* Micro USB female type 1* POGO Pins (for POS Base), including charging function 1* Micro SD 1* Micro HDMI 2* Barcode trigger 1* Power button
LEDs	1* red/green LED for power & system status
Power Adaptor	Input:100V to 240V AC 50/60Hz 1A Output: DC 12V 3A
Dimension	W x L x T: 278mm x 199mm x 20.9mm
Temperature	Operation temperature 0°C ~ 40°C Storage temperature -20°C ~ 60°C
Humidity	5% to 95% (no condensation)
Sealing	IP54
Drop specification	1M
Optional Device Module (Factory Option)	1D barcode scanner (laser) or 2D barcode scanner (image) IC card reader ISO7816 ; MSR ISO7811-Track 1, 2, 3 , Fingerprint 512dpi
Certification	CE/FCC/VCCI/BSMI/CCC

Accessories						
Item	PB-310	PB-320	PB-310-M	PB-320-M	CB-300	CB-310
Mechanism	POS Base Full	POS Base Full	POS Base Full Mini	POS Base Full Mini	Cradle Charging only	Cradle Full
USB	4	4	4	4	X	2
COM	4	4	4	4	X	1
Ethernet	1	1	1	1	X	1
Cash Drawer	1	1	1	1	X	X
DC in	12V 7.5A 90W	12V 15A 180W	12V 7.5A 90W	12V 15A 180W	12V 3A 36W	12V 3A 36W
Power USB	X	1*12V 1.5A 2*24V 2.3A	X	1*12V 1.5A 2*24V 2.3A	X	X
Dimension WxLxT(mm)	278*298.27*322.69	278*298.27*322.69	278*225.25*321.1	278*225.25*321.1	308.82*150.31*167.87	308.82*150.31*167.87

* specification subject to change without prior notice



Tablet POS solution with highly integrated peripherals to meet needs of all applications



Cradle and POS base options with different I/O port combinations



Stable and adjustable POS base with lock to firmly hold the tablet



Dual hinge design allows reading angle and height to adjust at ease



Hand Strap

PARTNER

CARE . TRUST . RESPONSIBILITY

Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX:+886-2-29153405
USA	TEL:+1-949-598-1888	FAX:+1-949-598-0088
Europe	TEL:+49 (0)40 450 635-0	FAX:+49 (0)40 450 635-130
UK	TEL:+44 (0)1928 579 707	FAX:+44 (0)1928 571 308
China	TEL:+86-21-67696667	FAX:+86-21-67696699
Africa	TEL:+27-11-700-7188	FAX:+27-11-700-7140
Middle East	TEL:+971-4-8862980	FAX:+971-4-8862980
Korea	TEL:+82-10-6404-8223	I-Phone:+82-70-4104-8223

E-mail:sales@partner.com.tw
E-mail:sales@partnertechcorp.com
E-mail:info@partner-tech.eu
E-mail:sales@partnertechuk.com
E-mail:sales@partnertech.com.cn
E-mail:sales@partnertech.co.za
E-mail:sales@partnertechme.com
E-mail:adams_c@partner.com.tw



Windows Embedded