

Handheld CCD barcode scanner

610nm~640nm Red LED

Features

CR6307A is designed for Retail / Warehouse use and it is the best accessory for POS, PC, and Mac computer.

CR6307A can read 1D codes on product quickly.

- * With quicker decode rate (300 scans/sec)
- * Ergonomic housing design
- * Multi-interfaces: USB HID, USB-Serial, RS232
- * Approved by CE, FCC, PAHS
- * will be applied supermarket, convenient stores, warehouse, or other retail stores.
- * Option: IrPD auto-sensing (CR6327A) & Stand



Scanners Specifications:

Model Name

CR6307A / CR6327A

Description

Cable / Auto-sensing

Ultra-long range CCD engine

Performance Characteristics

Light Source

<u> </u>	
Depth of field	Code39(5mil): 40mm~150mm
 (Based on 300 lux environment) 	nment.

(Based on 300 lux environment.)
There are +/- 1 cm tolerance)

EAN13 (13mil): 40mm~520mm

• Scan Rate 300 scans/sec

Best Resolution 4 mil
 Print Contrast ≥30%

Indicators
 LED & beeper

• Interface USB HID,USB Serial (by request), RS232(by request)

Auto-sensing
 Up to 180 mm (for CR6327A only)

Code 128,EAN-13, EAN-8,, Code 39, UPC-A, UPC-E,Codabar,

Interleaved 2 of 5, ISSN, ISBN,Code 93,MSI,Matrix 2 of 5,

Industrial 2 of 5,Code 11,RSS-14, RSS-14-limited,RSS-14-expand

Electrical Characteristics

Input voltage
 Current - Reading
 5 VDC ± 5%
 60mA

Physical Characteristics

• Dimension (L * W * H) 90 X 65 X 160 mm

• Weight 110 g +/- 5 g (No cable)

User Environment

Temperature-operation 0°C to 50°C
 Temperature-storage -10°C to 60°C
 Humidity-operation 5% to 95% non-condensing

Ambient Light
 100,000 Lux

Product specification is subject to change without notice.

RIOTEC CO., LTD. 8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL: +886-2-8647-1828 FAX: +886-2-8647-1800 E-mail: sales@riotec.com.tw Web: www.riotec.com.tw